



- Half-length PCI card
- Adapts a single-width PMC form factor to PCI/X
- Support 32/64 bit PCI Bus
- Supports both 33Mhz/66Mhz or extended
- Four 64-pin PMC connectors
- Compliant to IEEE P1386.1 Specifications
- Front or rear connection I/O access
- Universal 5V or 3.3V PCI Signaling
- LED indicators to indicate the Power supplies
- No software drivers are required

OVERVIEW

PCI to PMC is an adapter to install a PMC card into a PCI slot. Sometimes known as a carrier or converter PCI to PMC is a universal voltage 1/2 length PCI card, and will fit into standard desktop PC environment. The combination of PCI to PMC and mounted PMC will occupy a single PCI slot. Mechanically, a PMC card fits cleanly on a short-length PCI board, resulting in a highly acceptable delivery solution for desktop applications. It is recommended that this adapter be installed in a standard PCI-based system. Designed to host 32/64-bit PMC card, the PCI to PMC adapter requires no special bridge software to integrate PMC Mezzanine cards in to PCI systems. The extender supports 3.3V and 5V PCI bus signaling. The product will work with 33 MHz and 66 MHz clock speeds, and with 32/64-bit bus width. The carrier card acts simply as an adapter to route PCI bus signals to and from the PMC card through the PCI card slot edge connector. All AT's PMC cards and those from other vendors are supported. This board provides an easy and low cost solution that enables use of a PMC mezzanine I/O card in a standard PCI computer system. LED present indicators provide the detection of PMC card and the power supplies plugged onto the adapter card. This card is well suited for enterprise router/switch/gateway providers and system integrators.

Standard Usage

Mount the PMC card to the PCI adapter. Carefully grasp the upper edge of the adapter. Align the gold striped edge connector with the expansion slot socket. Press the board firmly into the socket. Make sure that the metal bracket provided is fixed firmly into the corresponding slot

Applications

- Fast, Simple Expansion
- Fast Integration of COTS or Custom I/O
- Ultra-high bandwidth to/from daughter boards

AT-PCI-PMC-Adapter

PCI Non-intelligent PMC Carrier Card

PRODUCT SPECIFICATIONS

Mezzanine Slots

- One PMC Slot
- 32bit, 33 MHz or 66MHz

Size

- Half size PCI card
- 32 bit PCI 2.1 Compliant

PMC Compatibility

- PMC compliant as per the IEEE 1386 specification

Interrupts

- INTA, B, C, D routed to PCI connector from PMC

VIO

- PCI IO Voltage is set by the PCI backplane. VIO is routed from the PCI connector to the PMC

Access Width

- Standard PCI byte lanes supported for byte, word and long access dependent on installed PMC
- 64 or 32 bit operation supported

LED's & Test Points

- Power indicator LED's

Environmental

- Operating Temperature: -40°C to +85°C
- Storage Temperature: -55°C to +100°C
- Relative Humidity: 5% to 95% (non-condensing)

Software Interface

- No software set-up required by PCI to PMC adapter

Warranty

- 1 Year warranty standard

ORDERING INFORMATION

Hardware Selection

AT-PCI-PMC-Adapter

Base Product

AT-PCI-PMC-Adapter = PCI to PMC Adapter Card

- Contact sales for support for other Operating Systems
- Contact sales for configuration of front and rear I/O configuration
- Contact sales for environmental options



ADTEC Electronics Inc.
144 Continente Ave , Suite #130
Brentwood, CA 94513, USA.
Ph : (408) 420 0646
www.adtecelectronics.com

Distributor/Reseller